PCMCIA CardBus 32Bit Gigabit 10/100/1000

Art-Nr: 7605269

www.m-cab.de

Standards and Protocols
- IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.1q, 802.1p
  CSMA/CD, TCP/IP

Interface
- 32-bit Cardbus

Transmission Rate
- 10 / 100Mbps for Half-Duplex mode
- 20 / 200 / 2000Mbps for Full-Duplex mode

Flow Control
- IEEE 802.3x Flow Control (Full-Duplex)

Jumbo Frame
- 7680Bytes

Port
- 10 / 100 / 1000Mbps RJ45

Network Media
- 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
- EIA/TIA-568 100O STP (maximum 100m)
- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)
- EIA/TIA-568 100O STP (maximum 100m)
- 1000Base-T: UTP category 5, 5e cable (maximum 100m)

LED Indicator
- 1000M Link/Act, 100M Link/Act

Safety & Emission
- FCC, CE

Environment
- Operating Temperature: 0?~40? (32?~104?)
- Storage Temperature: -40?~70? (-40?~158?)
- Operating Humidity: 10%~90% non-condensing
- Storage Humidity: 5%~90% non-condensing

Operating System
- Windows 95 / 98 / ME / NT4.0 / 2000 / 2003 / XP /
  Vista, Netware, Linux

Specifications are subject to change without prior notice. All tradenames referenced are registered namework of their respective owners.